

BOGE Model	Max. pressure		Effective free air delivery* 50 Hz		Effective free air delivery* 60 Hz		Motor power		Dimensions W x D x H mm	Weight kg
	bar	psig	m³/min	cfm	m³/min	cfm	kW	HP		
C 3 L	10	150	0.240	9	–	–	2.2	3.0	755 x 485 x 495	105
C 4 L	10	150	0.340	12	0.31	11	3.0	4.0	755 x 485 x 495	110
C 4 L	13	190	0.234	8	–	–	3.0	4.0	755 x 485 x 495	110
C 5 L	10	150	0.545	19	0.40	14	4.0	5.5	755 x 485 x 495	125
C 7 L	10	150	0.728	25	–	–	5.5	7.5	755 x 485 x 495	130
C 7 L	13	190	0.525	19	–	–	5.5	7.5	755 x 485 x 495	130

* Free air delivery figures in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure. Emitted sound pressure levels from 61 dB(A) according to DIN EN ISO 2151:2009

BOGE Model	Max. pressure		Receiver volume Litres	Effective free air delivery* 50 Hz		Effective free air delivery* 60 Hz		Motor power		Receiver option Litres	Dimensions W x D x H mm	Weight kg
	bar	psig		m³/min	cfm	m³/min	cfm	kW	HP			
C 3 LR	10	150	90	0.240	9	–	–	2.2	3.0	270	1130 x 490 x 920	155
C 4 LR	10	150	90	0.340	12	0.31	11	3.0	4.0	270	1130 x 490 x 920	160
C 4 LR	13	190	90	0.234	8	–	–	3.0	4.0	270	1130 x 490 x 920	165
C 5 LR	10	150	90	0.545	19	0.40	14	4.0	5.5	270	1130 x 490 x 920	175
C 7 LR	10	150	90	0.728	25	–	–	5.5	7.5	270	1130 x 490 x 920	180
C 7 LR	13	190	90	0.525	19	–	–	5.5	7.5	270	1130 x 490 x 920	185

* Free air delivery figures in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure. Emitted sound pressure levels from 61 dB(A) according to DIN EN ISO 2151:2009

BOGE Model	Max. pressure**		Receiver volume Litres	Effective free air delivery* 50 Hz		Effective free air delivery* 60 Hz		Motor power		Dimensions W x D x H mm	Weight kg
	bar	psig		m³/min	cfm	m³/min	cfm	kW	HP		
C 3 LDR	10	150	270	0.240	9	–	–	2.2	3.0	1700 x 590 x 1130	225
C 4 LDR	10	150	270	0.340	12	0.31	11	3.0	4.0	1700 x 590 x 1130	230
C 4 LDR	13	190	270	0.234	8	–	–	3.0	4.0	1700 x 590 x 1130	250
C 5 LDR	10	150	270	0.545	19	0.40	14	4.0	5.5	1700 x 590 x 1130	245
C 7 LDR	10	150	270	0.728	25	–	–	5.5	7.5	1700 x 590 x 1130	250
C 7 LDR	13	190	270	0.525	19	–	–	5.5	7.5	1700 x 590 x 1130	270

* Free air delivery figures in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure. Emitted sound pressure levels from 61 dB(A) according to DIN EN ISO 2151:2009

** Max. pressure of the compressor