

BOGE Type	Max. pressure		Effective free air delivery*		Motor power				Dimensions silenced W x D x H (mm)	Dimensions super-silenced W x D x H (mm)	Compressed air outlet	Weight silenced kg	Weight super-silenced kg
	bar	psig	m ³ /min	cfm	Main drive motor kW	HP	Fan motor kW	HP					
SL 270	8	115	33.3	1177	200	270	5.5	7.5	3100x1910x2145	3100x1910x2645	DN 100	3900	4000
SL 340	10	150	33.2	1173	250	340	7.5	10	3100x1910x2145	3100x1910x2645	DN 100	4500	4600
SL 340	13	190	33.0	1166	250	340	7.5	10	3100x1910x2145	3100x1910x2645	DN 100	4500	4600
SL 341	8	115	43.7	1544	250	340	7.5	10	3100x1910x2145	3100x1910x2645	DN 100	5000	5100
SL 431	10	150	43.4	1533	315	430	7.5	10	3100x1910x2145	3100x1910x2645	DN 100	5000	5100
SL 481	13	190	42.7	1508	355	480	7.5	10	3100x1910x2145	3500x1910x2645	DN 100	5600	5700

Emitted sound level as per PN8NTC2.3 from **78 dB(A)**.

* Free air delivery for complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure.